

Product Safety & Reliability Department
Telephone: 877-JLG-SAFE
Facsimile: 301-745-3713
E-mail Address: productsafety@jlg.com



An Oshkosh Corporation Company

Attn: Safety Manager or Service Manager

**Subject: Transferring to a Structure from the Platforms of JLG Products
While Elevated**

Pursuant to inquiries for information regarding the noted subject, the JLG Industries, Inc. Product Safety & Reliability Department submits the following:

JLG Industries, Inc. requires owner, user, operator, lessor and lessee compliance with all applicable regulations (employer, local, state, and national) pertaining to the utilization of Mobile Elevated Work Platforms (MEWP).

When transfer is necessary, enter/exit through the gate only with the platform within 1 foot of a safe and secure structure. 100% tie-off is also required in this situation utilizing two lanyards. One lanyard must be attached to the platform with the second lanyard attached to the structure. The lanyard connected to the platform must not be disconnected until such time as the transfer to the structure is safe and complete.

While there is no specific regulation regarding transfers, OSHA has provided to JLG the above information as the guidelines utilized by OSHA personnel.

The current owner, operator, and user is responsible for the safe and proper utilization of the subject MEWP. JLG Industries, Inc. assumes no responsibility or liability for any and all incidents involving personal injury, property damage, or equipment damage which may occur when transferring to a structure while elevated. Should you have any additional questions, please advise.

Sincerely,

JLG INDUSTRIES, INC.
Product Safety & Reliability Department