

3369LE Electric Scissor Lift



Fold-down handrails allow entry into low headroom areas

Proportional drive gives smooth control

One handed operation for operator comfort and control



Low maintenance non-skid steel platform with extension deck and Load Sensing System



Minimum hydraulic components reduce maintenance and operating costs

Rear axle oscillates when lowered travel is engage to assist in accessing difficult sites

240V AC battery charger with cut out to increase battery life

Rear electric drive motors, reduction hubs and spring applied brakes for maximum traction

Tie down and lifting lugs for ease of transport

Non-marking urethane filled lug tyres

8 x 6V deep cycle battery for quiet drive and lift operation

QUESTIONS TO ASK

- What are the ground conditions in the work area?
- What is the rated capacity needed for the job?
- Do you need an extension lead outlet in the platform?
- Do you need non-marking tyres?
- Is there power available on the site?

KEY SELLING POINTS

- Smooth control, proportional electric drive, with two speed ranges
- Oscillating rear axle for constant rear wheel traction
- Fold-down rails allows drive through standard 203cm door height
- Extension platform has fold-down rails
- Non-marking urethane filled tyres
- Constant traction 2 wheel drive for 35 per cent gradeability
- Wide scissor stack provides rigidity and stability
- Multi axis 4 degree level sensor
- Plug in JLG analyser to indicate system functions for servicing and adjustment
- Removable platform control box

APPLICATIONS

- Facilities maintenance
- Shopping centres and other indoor/outdoor areas
- Manufacturing and warehouse applications and stock-takes
- Electricians
- Plumbers
- Window installers
- All maintenance and construction work
- Factory fit outs

SPECIFICATIONS

Performance:

Platform Height (max.)	10.06m
Working Height	12.06m
Lift Time	38 sec
Lower Time	42 sec
Platform Capacity Standard	450kg

Dimensions:

Stowed Height – Rails Up	2.74m
Stowed Height – Rails Lowered	1.98m
Minimum Transport Length (Outriggers)	3.07 (3.81)m
Overall Width	1.75m
Wheelbase	2.32m
Ground Clearance	0.20m
Platform Width	1.65m
Platform Length	2.92m
Standard Platform Extension	0.91m
Platform Height Lowered	1.69m
Maximum Drive Height	10.06m

Power:

Power Source	Battery
DC Voltage	48V
DC Power	370 Amp h
Drive Motor - Type	DC Electric
Hydraulic Pump - Type	Gear
Batteries	8 x 6V

Travel:

Tyre Size	240/55 x 17.5
Tyre Type	Foam Filled/Non-marking
Inside Turn Radius	2.29m
Outside Turn Radius	4.88m
Drive Speed Elevated	0.64km/h
Gradeability	35%

Weights and Capabilities:

Hydraulic Tank Capacity	32 Ltr
Operating Weight	4,600kg