

ECOLIFT™ 50

NON-POWERED MAST LIFT

LOW-LEVEL
ACCESS LIFT



KEY SPECS

Platform Height
5-ft (1.50-m)

Rated Capacity
330-lb (150-kg)

Working Height
11-ft (3.50-m)

KEY FEATURES

- No hydraulics or batteries, requires less routine maintenance delivering more uptime and less overall cost of ownership.
- Easy maneuverability and lightweight design easily fits through most doorways and freight elevators.
- Safer, more ergonomic alternative to ladders - work comfortably with both hands and 360-degree range of motion.
- Patented, stored power lift/lower system lets you elevate with just the turn of a flywheel.
- Ideal for fit-out applications, areas with sensitive flooring and low ground bearing pressure requirements.

STANDARD SPECIFICATIONS

Performance

Working Height	11-ft / 3.50-m
Platform Height	5-ft / 1.50-m
Stowed Height	61-in / 1.55-m
Machine Width	28-in / 0.7-m
Machine Length	39-in / 0.98-m
Platform Size	28 x 24-in / 0.7 x 0.6-m
Rated Capacity	330-lb / 150-kg
Weight	432-lb / 196-kg
Maximum Gradient for Operation	0.5 Degrees
Maximum Gradient for Pushing	5 Degrees
Max Ground Bearing Pressure - Front	160 psi / 11.2-kg/cm ²
Max Ground Bearing Pressure - Rear	168 psi / 11.8-kg/cm ²
Wind Speed	0-mph

STANDARD FEATURES

- Lanyard Attach Point
- Steel Platform
- Frame-Mounted Bubble Level
- Integrated Fork Pockets
- Protective Wall Bumpers
- Self-Closing Saloon Style Entry Gate with quick pull-out pins for easy removal
- Plastic Tool Tray
- Non-Marking Wheels
- Auto-Braked When Entering Platform
- Auto-Locking Brake on Elevation
- Emergency Descent Rod
- Static Strap

ACCESORIES & OPTIONS

- Maintenance Tray with Slatted Design to Tether Tools
- Steel Tray Optional

ECOLIFT™ 50


NON-POWERED MAST LIFT

LOW-LEVEL
ACCESS LIFT



DIMENSIONS

All dimensions are approximate



- A.** Machine Height (Stowed) 61-in / 1.55-m
- B.** Machine Width 28-in / 0.7-m
- C.** Platform Width 24-in / 0.6-m



- D.** Machine Length 39-in / 0.98-m
- E.** Platform Length 28-in / 0.7-m
- F.** Rail Height 56-in



We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
JLG.com

An Oshkosh Corporation Company