

Model

POWERTOWER DUO

LOW-LEVEL ACCESS



The 2 person Powered Scaffold Tower

With a large work platform height of 3.1 m, a working height of 5.1 m and a 2 person, the safer and more efficient replacement for the Scaffold Tower is the Power Tower Duo.



Key Features

- Patented stabiliser deployment on elevation.
- Stabilisers interlocked preventing elevation until stabilisers deployed correctly.
- 2 person capacity.
- 3.1 m platform height, 5.1 m working height
- 250 kg safe working load (2 persons pls tools)
- Compact - Only 0.78 m wide, passes easily through standard doorways
- Large 1.52 x 0.75 m platform size
- Only 0.78 x 1.6 m working footprint
- Easy access gate

PUSH AROUND

Indoor use

Working Height: 5.1 m

Applications: Dry-lining. Pipe & Ductwork. Air conditioning. M&E. Shopfitting. Painting.



Model POWERTOWER DUO

LOW-LEVEL ACCESS

Specifications

OPERATING DIMENSIONS

Maximum working height:	5.10 m
Maximum platform height:	3.10 m
Platform dimensions:	1.52 x 0.75 m
Working foot print:	1.60 x 0.78 m
Safe working load:	250 kg

CLOSED DIMENSIONS

Length:	1.60 m
Width:	0.78 m
Height:	1.85 m
Weight:	342 kg

POWER OPTIONS

Battery:	12V c/w automatic charger.
Mains:	110V or 230V.
Controls:	Simple push button basket controls.

OTHER FEATURES

Construction:	Heavy duty fabricated steel superstructure, stainless steel brushed pivots, tough powder coated finish.
Safety:	CE marked, complies fully with EN280 and relevant European machinery directives. Full fail-safe hydraulics, automatic locking wheels.
Options:	Tilt alarm c/w auto cut-out. Pipe Carrying kit (max 2" pipe). Tool tray. Foam buffer kit.

Safety features

- Fail-safe hydraulic circuit complete with check valve on lift cylinder
- Patented stabiliser deployment on elevation
- Stabilisers interlocked preventing elevation until stabilisers deployed correctly
- Emergency descent from ground level
- Audible ascent and descent drive alarm



IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV

Polaris Avenue 63
2132 JH Hooftdorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 3750
www.jlg.com

An Oshkosh Corporation Company