

1030P

PUSH-AROUND MAST LIFT

LOW-LEVEL ACCESS



STANDARD SPECIFICATIONS

Performance

Platform Height	10-ft 2-in / 3.10-m
Working Height	16-ft 2-in / 5.11-m
Overall Height	6-ft 1-in / 1.85-m
Platform Entry Height	29-in / 74-cm
Platform Size (LxW)	60-in x 29.5-in / 1.52-m x .75-m
Overall Machine Length	64-in / 1.63-m
Overall Machine Width	31-in / 0.79-m
Weight	805-lb / 365-kg
Platform Capacity	550-lb / 249-kg
Maximum Gradient for Operation	0.5 Degrees
Maximum Gradient for Pushing	5 Degrees
Max Ground Bearing Pressure	174 psi
Max Wind Speed Rating	0 mph / 0 m/s - Indoor Use Only

Power Source

Batteries	12V AGM
Battery Charger	Automatic 110V-240V Charger

KEY SPECS

Platform Height
10-ft 2-in / 3.10-m

Platform Capacity
550-lb / 249-kg

Working Height
16-ft 2-in / 5.11-m

KEY FEATURES

- Access More Work - Large 29.5 x 60-in. platform provides access to more workspace without needing to reposition the unit
- Improve Operator Comfort - Platform position creates more ergonomic working conditions compared to ladders and scaffolding
- Carry More Tools and Materials - 550-lb platform capacity increases productivity and reduces operator fatigue
- Operate on Sensitive Flooring - Lightweight design combined with low ground-bearing pressure makes this machine ideal for sensitive floors

STANDARD FEATURES

- Auto-Lok Wheels on Elevation
- Battery Charge Indicator
- Emergency Descent
- Frame-Mounted Bubble Level
- Heavy Duty Lifting Cantilever Mast
- Hour Meter
- Integrated Fork Pockets
- Load Sensing System
- Non-Marking Wheels
- Self-Closing Platform Gate
- Static Strap

1030P

PUSH-AROUND MAST LIFT

LOW-LEVEL ACCESS



- | | |
|----------------------------|--------------------|
| A. Machine Height (stowed) | 6-ft 1-in / 1.85-m |
| B. Machine Width | 31-in / .79-m |
| C. Platform Width | 29.5-in / .75-m |
| D. Machine Length | 64-in / 1.63-m |
| E. Platform Length | 60-in / 1.52-m |



We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
JLG.com

An Oshkosh Corporation Business