

ALL-NEW

ES2632M MICRO-SIZED SCISSOR

The max 25-ft 6-in platform height and compact design with zero turn radius and QuikFold rails provide peak job site maneuverability and access, while JLG® exclusive tech such as Variable Tilt and Progressive Elevated Drive ensure job site productivity.



QUIKFOLD RAILS

RAILS FOLD DOWN IN SECONDS TO TRAVERSE AROUND THE JOB SITE FOR EFFICIENCY

OPTIONAL INTEGRATED MID-RAIL DECK

ENCLOSED, FOUR-RAIL SYSTEM PROVIDING 19.5-IN OF ADDITIONAL ACCESS HEIGHT

LEAK CONTAINMENT

COMES STANDARD TO PROTECT DELICATE WORK SURFACES

CLEARSKY SMART FLEET™

INDUSTRY-FIRST TWO-WAY DATA TRANSMISSION EVOLVES ONE-WAY CONNECTIVITY INTO TRUE FLEET INTERACTIVITY.

ZERO-TURNING RADIUS

FOR NAVIGATING TIGHT JOB SITES

VARIABLE TILT TECHNOLOGY

JLG EXCLUSIVE TECHNOLOGY THAT ALLOWS OPERATORS TO ELEVATE TO FULL HEIGHT ON LIMITED SIDE SLOPES.

PROGRESSIVE ELEVATED DRIVE

AUTOMATICALLY ADJUSTS DRIVE SPEED BASED ON PLATFORM ELEVATION TO INCREASE PRODUCTIVITY

ADDITIONAL FEATURES

- 600-LB PLATFORM CAPACITY* [2 OCCUPANTS INDOOR / 1 OUTDOOR]
- 25-FT 6-IN INDOOR PLATFORM HEIGHT [18-FT OUTDOOR]
- FITS THROUGH STANDARD DOORWAYS
- AC DRIVE AND DRIVE MOTORS COME STANDARD

*Capacity reduced to 550-lb with Integrated Mid-Rail Deck

