

MEWP SURFACE PROTECTANT TOOLS & SUPPLIES



HELP PROTECT YOUR EQUIPMENT INVESTMENT

MEWP Protector is a biodegradable, water-based, transparent film designed to help reduce the impact of overspray on surfaces. Applied as a liquid, it conforms to a variety of surface shapes, forming a non-tacky barrier. The coating can provide overspray protection while wet and is designed to be removed with water.

FEATURES AND BENEFITS:

- Helps cover hard-to-reach areas
- Designed for fast application with spray equipment
- Water-soluble formulation
- Adapts to a range of surface shapes
- Dries to a non-tacky film



APPLICATION INSTRUCTIONS

Ensure surfaces are clean and dry. Freshly painted surfaces should be fully cured. Mask any areas not intended for coating.

1. Apply a continuous, medium-wet coat (3–4 mils) to non-porous surfaces. Use a well-maintained HVLP spray gun with stainless steel fluid passageways and a 1.8 mm–2.5 mm tip.
2. Remove masking while the coating is still wet. Wipe excess overspray with a damp sponge if needed.
3. Allow coating to dry until no longer wet to the touch. Air movement may help reduce drying time. In higher humidity, the dried film may remain somewhat soft.
4. Clean spray equipment with warm water immediately after use.

REMOVAL INSTRUCTIONS

Using a hose or pressure washer, wet coated surfaces and allow to soak for several minutes. Heavier overspray areas may be wiped with a wash mitt or brush. Rinse surfaces again. After drying, coating may be reapplied if needed.

DESCRIPTION	PART NUMBER
MEWP-Surface Protector, 5-GA	7019707
MEWP-Surface Protector, 55-GA*	7025421

*Only available as direct ship.

ORDER TODAY | onlineexpress.jlg.com | allfleet@jlg.com

PART NO. 401190 | R0326_01



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
[JLG.com](https://www.jlg.com)

An Oshkosh Corporation Business