

MEWP SURFACE PROTECTOR SUPPLIES



Protect Your Investment

Protect your investment the right way. MEWP Protector is completely biodegradable, water based, transparent overspray-protecting film. It goes on as liquid and conforms to any surface or shape, in effect sealing the surface with a non-tacky film. MEWP Protector demonstrates the unique ability to provide significant overspray protection while wet. Removes easily and quickly with water.

Features and Benefits Include:

- Effectively masks hard-to-reach areas
- Fast, easy application with spray equipment
- Environmentally safe and water-soluble
- Conforms to any surface shape



Application:

1. Surface must be dry. Freshly painted surfaces must be fully cured. Mask any surfaces you do not wish to cover.
2. Apply continuous, medium wet coat (3 to 4 mils) to all non-porous surfaces to be protected. Use a well-maintained HVLP gun with stainless steel fluid passageways and a 1.8mm to 2.5mm spray tip.
3. Remove any masking while coating is still wet. Use a damp sponge to wipe any excess overspray.
4. Allow coating to cure so that it is no longer wet to touch. Air movement speeds dry time. Note that in high humidity environments the dry film will tend to be slightly soft.
5. Clean spray gun immediately with warm water.

Removal:

Using a hose or pressure washer, spray water onto all coated surfaces and allow to soak for a couple minutes. Scrub heavy overspray areas with a wash mitt or brush. Rinse surfaces again. When all surfaces are dry, re-apply coating.

Description	JLG Part Number
MEWP-Surface Protector, 5 Gallons	7019707
MEWP-Surface Protector, 55 Gallons*	7025421

**At this time 55 Gallons of AWP are only available as direct ship.*

Order Today

Online: onlineexpress.jlg.com

Call: 1-877-554-5438 | **Fax:** 1-800-733-8939



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
JLG.com
An Oshkosh Corporation Company