

ES1230

DRIVABLE VERTICAL MAST LIFT

VERTICAL MAST LIFT



KEY SPECS

Platform Height
12-ft / 3.66-m

Machine Width
2-ft 6-in / 76-cm

Platform Capacity
500-lb / 227-kg

Stowed Drive Speed
3 mph / 4.8 km/h

KEY FEATURES

- Increased productivity with longer running time than any lift in its class while offering a 500-lb platform capacity.
- Ultra-compact, lightweight design allows for ease of transport in freight elevators and is ideal for work on sensitive flooring.
- Tackle maintenance jobs efficiently with the reliable electric drive.
- Low maintenance, energy efficient and environmentally clean.

ACCESSORIES & OPTIONS

- 213 Amp Hour AGM Batteries
- 900W – AC Inverter/charge
- Ambient Adjusting Alarm
- Anti-Vandalism Package (Control Box Cover Assembly)
- Flashing Amber Beacon
- Platform Control Extended Length
- Programmable Security Lock
- White Noise Alarm

STANDARD SPECIFICATIONS

Performance

	Indoor Only
Platform Height (Elevated)	12-ft / 3.66-m
Platform Capacity	500-lb / 227-kg
Lift / Lower (No Load)	15 / 21 seconds
Lift / Lower (Rated Load)	17 / 25 seconds
Maximum Drive Height	Full Height
Weight*	1,775-lb / 805-kg
Drive Speed (Lowered)	3 mph / 4.8 km/h
Drive Speed (Elevated)	0.5 mph / 0.8 km/h
Gradeability	25%
Turning Radius (Inside)	4.4-in / 11.2-cm
Turning Radius (Outside)	4-ft 10-in / 1.46-m

*Certain options or country standards increase weight

Power Source

Charger	20 Amp Automatic (120V/240V – 50/60 HZ)
Batteries	4 x 6V 220 amp-hr
Drive	24V Electric

Tires

Standard	100 x 323 Non-Marking Solid
----------	-----------------------------

Brakes

Electric, Friction (On Drive Wheels)

Hydraulic System

Capacity	1.88 gal / 7.1 L
----------	------------------

STANDARD FEATURES

- All Motion Alarm
- All-steel Platform Deck and Rails
- Automatic Traction Control
- Battery Condition Indicator
- Controls and Electrical System Common with ES Series Scissor Lift
- Corner Tool Tray
- Horn
- Hourmeter
- Industry Leading Duty Cycles
- Integrated Lifting and Tie-down Points
- Joystick with Fully Proportional Lift and Drive
- Lanyard Attachment Points
- Machine Can be Lifted by Forks from Either Side
- Mechanical Pothole Protection System
- Powder Paint Coating
- Saloon-style Entry Gate
- Standard 110 V AC Wiring to Platform
- Steel Swing-out Battery Doors with Heavy Duty Hinges
- Tilt Alarm and Light

ES1230

DRIVABLE VERTICAL MAST LIFT

VERTICAL MAST LIFT



DIMENSIONS

All dimensions are approximate



A. Machine Height	5-ft 5-in / 1.66-m
B. Platform Width	27-in / 68-cm
C. Platform Length	33-in / 84-cm
D. Machine Width	2-ft 6-in / 0.76-m
E. Machine Length	4-ft 6-in / 1.36-m
F. Wheelbase	3-ft 5-in / 1.04-m
G. Ground Entry Height	1-ft 10-in / 56-cm
H. Ground Clearance	2.6-in / 6.6-cm



We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
JLG.com

An Oshkosh Corporation Business